



Concrete & Plaster Bond™

A primer for JETaFLOW, improves bonding for cement-based toppings, patches, stucco, plaster, gypsum, and masonry

Repair Thickness

Up to 10 mils

Set Time

1 hour

Application Technique

Broom, Brush, Roller, Spray

Where to Use

- Indoors or outdoors
- Where added bond strength required
- Bonding new concrete to old
- Plaster bonding or primer

Features

- Easy to apply
- Long lasting formula
- Will not re-emulsify
- Breathable
- Highly versatile
- Self-bonding/self-curing
- Water will not affect the dry bond
- Chemical resistant

Packaging and Yield

1 gallon Up to 150 ft², concrete
Up to 300 ft², plaster

Product Description

Concrete & Plaster Bond™ is a special water-based bonding agent designed to improve bonding for cement-based materials, stucco, plasters, gypsum and masonry. Once **Concrete & Plaster Bond** dries clear, topping can be applied immediately or up to 3 days later.

For Best Results

Apply to a clean, dry, sound substrate above 50° F. Check moisture content (mat test) prior to applying. Allow product to dry clear before topping. Do not retemper already mixed material. Do not expose to rain or flowing water during application. **Concrete & Plaster Bond** is to be stored in a dry, cool place. Do not allow product to freeze.

Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete substrate shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign matter. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

Application

Concrete & Plaster Bond should be brush or broom applied, taking care to avoid puddling. It has a milky white appearance and should be allowed to dry clear before topping.

Curing

Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Contact JE Tomes if you have any questions or concerns with your application.

Warning

KEEP OUT OF REACH OF CHILDREN. If eaten or swallowed, serious personal injury could occur. Prolonged contact with skin may cause irritation. In case of eye contact, flood eyes repeatedly with water. Consult your physician under any of the above circumstances.

LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JETOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.



Concrete & Plaster Bond™

Technical Data

Tensile bond strength, 3 day	487 psi	ASTM C932
Vibration testing	Various toppings	Excellent
Failure occurred in topping—No bond line failure		